a,,-measurement get it started!

For more than 50 years Novasina cosmetics. Thanks to a longstanding is the leader in the production of experience and research and develprecision instruments for water ac- opment we are able to offer today tivity measurement in foodstuff, reliable, high quality "Swiss made" processed food as well as pharma- products that set new standards in ceutical, chemical products and the water activity measurement.

tart -aw

Simple water activity measurement device



good start is essential for every project and undertaking. That is why the LabStart-aw has been developed to introduce quality managers, production personnel and laboratory technicians to water activity measurement. This instrument is simpleto- operate, providing basic measurement functions, yet still having built-in automatic equilibrium detection and the well-proven resistive-electrolytic sensor technology as employed in all Novasina water activity meters. As standard, the LabStart-aw is supplied with one re-useable humidity calibration standard which provides a very economical solution to precision water activity measurements in one simple kit. Furthermore, the calibration standard is an easy method for verification of the instrument's high performance.

Optional chemical protection filters assist with high solvent - content samples, as well as accurate water activity detection with high repeatability.

Although the LabStart-aw is a starter instrument, it offers great value, is simple and easy-to-use. Are you ready to begin your water activity measurements?

Advantages:

- Fast and precise aw-measurement thanks to the worldwide unique "Novalyte" measurement technology
- Automatic equilibrium detection for improved measurement reliability
- Re-usable SAL-T humidity standards and long-life sensor for economy
- Specific chemical sensor protection filters available
- Calibration data is stored on the sensor
- Checking, testing and adjusting possibilities (SAL-T humidity standards)
- Housing with stable and robust base plate





Simple and easy a_w-measurement instrument LabStart-aw

The Art of Precision Measurement

Neuheimstrasse 12 CH-8853 Lachen SZ Tel: +41 (0)55 642 67 67

Fax: +41 (0)55 642 67 70

info@novasina.ch / www.novasina.com

Specifications LabStart-aw:

	A _w -value	Sample temperature	
Measuring principle :	Resistive - electrolytic	NTC (only)	
Measuring range :	0.03 1.00 a _w	1530 °C (5986°F)	
Accuracy: Range :	+/- 0.03 a 0.20 0.80 a _w (2080% rh)	+/- 0.15 °K 0 +50°C	
Resolution :	0.01 a _w	0.1 °C	
Accuracy of temp. control :	no temperature control available		
Repeatability a _w :	+/- 0.01 a _w		
Mains supply :	5 VDC +/- 6% max. power requirement : 4 W		
Power supply :	90264 VAC 50 / 60 Hz, output -> +5 VDC		
Display :	Reflective, high contrast LC-Display, dimensions: 35 x 69mm		
Operating :	3x multi-function keys including ON/OFF		
Communication :	no communication opportunities		
Housing:	Two-part PC/ABS design housing, measurement chamber aluminium anodized		
Weight:	2.8 kg, dimensions approx. : 300 x 200 x 105 mm		
Protection class :	IP 22		
Sample volume	21.1 ml standardised sample	dishes	
Measuring chamber :	40 x 12 mm Spring-loaded measurement head		
Special feature :	Intelligent "Novalyte" measurement sensor CM-4 with calibration point memory		

260 0992



Order code LabStart-aw

Accessories + Options	Article-Nr.
Replacement sensor CM-4	260 0995
Power supply universal plug	260 0505
Protection filter REDOX	111 7212
Protection filter eVC-21	111 1001
Protection filter eVC-26	111 1003
Protection filter eVALC	111 0995
Pre-filter white 5 pieces	260 0183
Tension ring	260 0210
ePW sample dishes 100 pieces	111 0601

Humidity/aw Standards	Article-Nr.
Humidity Check SAL-T 58% RH	260 0189
Humidity Check SAL-T 75% RH with UKAS certificate:	111 0936
Humidity Check SAL-T/C 58% RH	260 0190
Humidity Check SAL-T/C 75% RH	111 1063



